

# **PRODUCT DATA SHEET**

### PRODUCT DESCRIPTION

# **Duckhams Classic Q 20W-50**

Classic Q 20W-50 is a robust mineral engine oil designed for older engines and high-load operating conditions. It offers strong film strength, thermal stability, and protection, making it ideal for classic vehicles or those operating in hotter climates. The formulation helps reduce oil consumption and maintain engine cleanliness even under demanding use.



# **FEATURES AND BENEFITS**

- Provides reliable protection in high-temperature and heavy-duty conditions
- · Helps minimize engine wear and extend engine life
- Maintains performance and stability during long drives or towing
- Reduces oil consumption in older or high-mileage engines
- Supports engine cleanliness by limiting buildup and deposits
- Ideal for vintage cars and vehicles operating in warmer environments

## **SPECIFICATIONS:**

API CC/SF MIL-L-2104B



# **PRODUCT DATA SHEET**

#### TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity		20W-50
Density @ 20°C	Kg/m³	0.881
KV100	cSt	18.5
KV40	cSt	162.3
VI	-	131
CCS	сР	6689
TBN		6.6
Sulphated Ash	%	1.5
Colour		Clear Amber
Flash (Closed)	°C	223
Pour Point	°C	-9

# **HEALTH, SAFETY AND ENVIRONMENT**

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

#### STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.