



Performance 20W-50 | Mineral Engine oil

Property

- best resistance to oxidation (ageing stability)
- compatible with all seal materials (old and new)
- keeps the engine clean and protects against wear and corrosion
- excellent high temperature properties
- protects against premature ignition at low speed (LSPI → Low Speed Pre-Ignition)

Application area

- guaranteed lubrication reliability, including for motor sport use
- suitable for classic cars
- suitable for catalytic converters
- can be used in motor sport
- suitable for cars

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Property	Unit	Value
Viscosity SAE	-	20W-50
Color	-	brown
Viscosity @ 40°C	cSt	151
Viscosity @ 100°C	cSt	18
Viscosity index	-	132
Density @ 15°C	kg/l	0.87
Viscosity CCS @ -15°C	mPa·s	7330
Zinc content	ppm	1050
Pour Point	°C	-25
Flash Point	°C	218

Available packaging

1 L bottle	Case 12 x 1 L bottles
54 kg drum (approx. 62 L)	180 kg drum (approx. 207 L)

Specifications

ACEA A2/B2*, A3/B3*, A3/B4
API SL*, SM*, SN*, SN Plus*, SP
MB 229.1
VW 500 00*, 501 01, 505 00

* Additional Specifications